



**ThinnerTede**

**LABORATORIO DE CONTROL DE CALIDAD  
ESPECIFICACIÓN TÉCNICA**

**PRODUCTO: EXXOLD40  
CÓDIGO: DILUYENTE 40**

ANÁLISIS	TIPO	MÉTODO	RESULTADO	UNIDAD	LOWER	UPPER
APPAR	APPAR	ASTM D-4176(A)	CL&B			
AROMATIC	AROM%	AM-S 140.31	0.1	WTPCT		1.00
COL-SAY	COL-SAY	ASTM D156	>30-		30	
DIST-D86	DRY-PT	ASTM D-86	199.0	DEG.C	190.0	205.0
DIST-D86	IBP	ASTM D-86	168.9	DEG.C	160.0	170.0
50% VOL		ASTM D-86	175.6	DEG.C		180.0
FLASHTAG	FLASH-T	ASTM D-56	48.0	DEG.C	40.0	
H2O/KF	H2O%	ASTM D-1364	0.003	WTPCT		0.0500
S-PPM		ASTM D-4045	<1.0-	PPM		5.00
SP-GVITY	SP-GVTY	ASTM D-4052	0.7759	G/ML	0.7600	0.8100
IBATCH			1			

José Zabala 845 (1619), Garín, Prov. de Buenos Aires, Argentina.

Tel: (0348) 445-8008/8734/8735 / (15) 3181-3802/3805 / 3220-1550/1551/1552/1553

[info@thinnertede.com](mailto:info@thinnertede.com) - [www.thinnertede.com](http://www.thinnertede.com)